

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
12 May 2005 (12.05.2005)

PCT

(10) International Publication Number  
**WO 2005/042180 A1**

(51) International Patent Classification<sup>7</sup>: **B21D 22/14**

(21) International Application Number:  
PCT/NL2004/000776

(22) International Filing Date:  
4 November 2004 (04.11.2004)

(25) Filing Language: Dutch

(26) Publication Language: English

(30) Priority Data:  
1024697 4 November 2003 (04.11.2003) NL

(71) Applicant and

(72) Inventor: MASSÉE, Johan [NL/NL]; Vijfsprongweg  
104, NL-6741 JC LUNTEREN (NL).


(74) Agents: AALBERS, Arnt, Reinier et al.; Overschiestraat  
180, NL-1062 XK AMSTERDAM (NL).

(81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: METHOD AND FORMING MACHINE FOR DEFORMING A WORKPIECE



(57) Abstract: The invention relates to a method and a forming machine for deforming a workpiece, such as a metal cylinder or plate (3), by means of a tool, in particular one or more forming rollers (5), wherein the workpiece and/or the tool are rotated about an axis (4) relative to each other, the tool move; through one or more deforming curves and at least part of the workpiece is deformed. During the deforming process, values of one or more coordinates of the position of the extreme: edge of the workpiece are measured, and one or more parameters of the deforming process is/are changed on the basis of the measured values.



**Published:**

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*